

DECLARATION OF PERFORMANCE

Nro. 001.CPR.607030

1. Unique identification code of the product-type:

Kerabit Sokkelilevy

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

3.

| Size | Item number | EAN-code |
|----------|-------------|---------------|
| 1 x 20 m | 607030 | 6417547070306 |
| 2 x 20 m | 607031 | 6417547070313 |

(lot no. see label and product)

4. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

damp proofing sheets, type V (EN 13967).

5. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Nordic Waterproofing Oy
Rälssitie 6, 01510 Vantaa
Tel. +358 10 851 1000, www.kerabit.fi

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

AVCP 2+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The Notified Body authorized for the FPC Nr. 1213 – SKZ Testing GmbH executed the initial inspection of the production site and of the FPC, as well as the continuous surveillance, the determination and evaluation of the FPC and released the certificate of conformity of the FPC (Nr. 1213 - CPR – 7285).

9. Declared performance

| Essential characteristics | Performance | Test standard | Harmonized technical specification |
|--|--|---|------------------------------------|
| Water tightness (60 kPa, 24 h) | W1 | EN 1928 | EN 13967:2012 |
| Nail shank tear resistance MD/CMD | 120 N | EN 12310-1 | |
| Joint tensile shear resistance | NPD* | EN 12317-2 | |
| Resistance to impact, method A | 450 mm | EN 12691-2 | |
| Tensile strength MD/CMD | 250/250 N/50 mm | EN 12311-2 | |
| Elongation MD/CMD | 25/20 % | EN 12311-2 | |
| Resistance to static load | 20 kg | EN 12370 | |
| Reaction to fire | Class F | EN ISO 11925-2, classification to EN 13501-1 | |
| Watertightness, durability after ageing | Pass | EN 1296 / EN 1928 | |
| Watertightness, durability after chemical ageing | Pass | EN 1847/EN 1928 | |
| Dangerous substances | Less than required by national regulations in EU Member States | National Regulations in force in EU Member States | |

* NPD (No Performance Determined)

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Lohja 16.3.2020



Pertti Nurmi
Development and Quality Manager
Nordic Waterproofing Oy